



J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

TERMINAL PART NUMBER	SIM-01-110A
STRIP LENGTH (MM)	4.5

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
0.20 mm ²	1.20	2.40	*	3.20	RE:BS5057
0.30 mm ²	1.25	2.40	*	3.20	RE:BS5057
0.50 mm ²	1.30	2.40	*	3.20	RE:BS5057

COMMENTS:

* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05
CONDUCTOR WIDTH - +/- 0.05
INSULATION HEIGHT - N/A
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
AJS	MS
29-01-01	29-01-01