



## J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

<b>TERMINAL PART NUMBER</b>	SJ2M-01GF-M1.0N
<b>STRIP LENGTH (MM)</b>	3.5 – 4.0 mm

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS) minimum
	HEIGHT	WIDTH	HEIGHT	WIDTH	
24 AWG	0.80	1.60	*	1.90	30.0N
22 AWG	0.85	1.60	*	1.90	45.0N
20 AWG	0.95	1.60	*	1.90	75.0N

### COMMENTS:

\* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

### GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05  
CONDUCTOR WIDTH - +/- 0.05  
INSULATION HEIGHT - N/A  
INSULATION WIDTH - +/- 0.05

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
PDS 22-04-05	PDS 22-04-05