



J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

TERMINAL PART NUMBER	SJ2M-21GF-M1.0N
STRIP LENGTH (MM)	3.5 – 4.0 mm

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS) minimum
	HEIGHT	WIDTH	HEIGHT	WIDTH	
22 AWG	0.93 +/- 0.05	1.60	*	1.85	45.0N
20 AWG	1.03 +/- 0.05	1.60	*	1.85	75.0N
0.75 mm ²	1.03 +/- 0.03	1.60	*	1.85	80.0N

COMMENTS:

* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

GENERAL TOLERANCE:

CONDUCTOR HEIGHT - See Above
CONDUCTOR WIDTH - +/- 0.05
INSULATION HEIGHT - N/A
INSULATION WIDTH - +/- 0.05

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
PDS	PDS
22-04-05	22-04-05