


## **SPLICE FOR HEATER WIRES**

## Splices for vinyl-insulated wires and heater wires



Insulated wire connection	
Heater wire connection section	>

This splice is used to connect a vinylinsulated wire to a defrosting heater wire of a refrigerator or a freezer. The barrel of the splice has a lid feature that prevents the heater wire from being damaged or broken during crimping. This ensures a reliable and stable connection. Various heater connectors are also available.

Model No.	Applicable wire(reference)	Finish	Q'ty / reel			
SHC-21-001	Heater wire + Vinyl-insulated wire	-				
SHC-21T-001	(Thin insulation) (0.3~0.75mm <sup>2</sup> )	Tin-plated	F 000			
SHC-21-002	Heater wire + Vinyl-insulated wire	-	5,000			
SHC-21T-002	(Thick insulation) (0.3~0.75mm <sup>2</sup> )	Tin-plated				
Material						
	Brass					

## **RoHS compliance**

Note: Before use, the performance of this splice must be tested with the wire that is to be used.

	Contact	Crimping	Applicator		
		machine	Crimp applicator	Dies	Crimp applicator with dies
SH	IC-21(T)-001	AP-K2N	MKS-L-HC	MK/SHC-21-001/002	APLMK SHC21-001/002
SH	IC-21(T)-002		_	—	—

\* Compliant with RoHS.

- \* Refer to "General Instruction and Notice when using Terminals and Connectors" at the end of this catalog.
- \* Contact JST for details.